

## CAST red IP67 manual call point, surface mounting

Part No. **CA47067**



### Overview

A high-quality IP67 rated surface-mounting red manual call point for use with C-TEC's XFP&ZFP 'CAST' protocol Addressable Fire Panels.

LPCB certified to EN54 Parts 11 & 17.

Onboard short-circuit loop isolator.

Smooth-action resettable element mimics the feel of breaking glass.

Supplied with reset/back box removal key and 'Not in Use' label.

Red LED 'alarm ring' illuminates call point face upon activation.

Photoluminescent operating window remains visible for up to 5 minutes.

Low current draw - just 460µA @ 35V DC.

### More Information

CAST' is the world's most-advanced 'distributed intelligence' fire alarm system protocol. Conceived, designed and realised by C-TEC as part of a five-year, multi-million pound project, it involved the creation of a powerful proprietary communication protocol (C-TEC Addressable System Technology, CAST) and multiple control panels & field devices. Now available to purchase, its key features include:

255 devices per loop.

Autonomous decision-making for faster response times.

Multiple type codes.

40V loop drive voltage.

Two 'soft' addressing options - automatic via the panel or manual via a powerful handheld programmer.

Powerful multi-level addressing facilitates easy device addition and swapped device identification.

Multiple functionality at a single address (integrated devices).

Volumes, tones & detector modes can be changed at compatible panels.

High-speed data transmission and robust data transfer.

Intrinsically EN54-13 compliant.



Provides geographical location of short and open circuit faults (a short circuit isolator is included as standard in every CAST field device).

Replace device function.

Future seamless integration with other CAST life safety systems reducing energy, servicing, installation and repair costs.

Designed and manufactured in the UK.

## Technical Specifications

Approvals/certifications	Certified to EN54 Parts 11 & 16 by the LPCB.
Compatibility	Compatible with C-TEC's XFP/ZFP CAST Protocol Addressable Fire Panels.
Application/operation	Surface mounting only.
Supply/operating voltage	27 to 40V DC.
Quiescent current	370µA @ 35V DC.
Alarm current	5mA.
Indicators	Red 'alarm ring'. Lit steady red (when activated) and flashing Red (when polling)
Connections	Loop IN, Loop OUT (x2).
Product dimensions (mm)	87 W x 88 H x D 72mm (includes back box).
Construction & finish	Red ABS polycarbonate; Glass fibre window.
IP Rating	IP67.
Weight	228g.
Operating conditions/temperature	-10°C to +55°C.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



**T** 01942 322744    **E** [sales@c-tec.co.uk](mailto:sales@c-tec.co.uk)  
**F** 01942 829867    **W** [www.c-tec.com](http://www.c-tec.com)



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom