

All fires, fast

firexo

# FIREXO 2LTR EXTINGUISHER

Model/Product Number 809-765-347-846

Name	Firexo 2LTR extinguisher
Model/Product number	809-765-347-846
Capacity (litres)	2
Cylinder Height (mm)	405
Outer Diameter (mm)	340
Cylinder Material	Steel
Pressurizing Gas	Nitrogen
Test Pressure (bar)	30 bar
Working Pressure at 20 °C	12 bar
Weight Full (kg)	3.82
Weight Empty (kg)	1.4
Spray Range (m)	1 – 3
Discharge Time at 20 °C (seconds)	20 – 30
Temperature Range ( °C)	minus 5 / plus 60
Warranty	5yr
Fire Rating	13A/34B/C/D/E/25F
CE Approval	Yes



## ALL FIRES.



### METHOD OF USE

Discharge entire contents onto the fire from at least 1 metre distance. Do not use if pressure indicator enters red and check weight and service once a year. Check periodically and change or recharge after use. Firexo extinguishers should be serviced once a year by an approved Firexo service engineer in accordance with BS5306. Recharging should be carried out to BS 5306-9:2015 only using recommended components from Firexo. Safe for use on electrical fires to 35 kV.

© FIREXO 2019

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.

firexo