

DOORMOUSE

WALL MOUNTED
ELECTROMAGNETIC FIRE DOOR HOLDERS

- 24Vdc OR 230Vac SUPPLY VOLTAGE
- ZERO RESIDUAL FORCE
- 200N 500N HOLDING FORCE
- FIRE RESISTANT ABS CASING
- APPROVED TO EN1155 AND CE MARKED
- HIGH QUALITY COST EFFECTIVE PACKAGE
- INCLUDES FITTING INSTRUCTIONS
- UL LISTED VERSION AVAILABLE FILE R25547




Electromagnetic fire door holders are designed to hold open fire doors in any areas where easy access is essential in relation to the Equality Act, and can be used in conjunction with any suitable fire alarm systems. When an alarm is triggered, power to the door holder is cut, allowing the fire door fitted with it's standard closing mechanism, to shut automatically. Doormouse door holders are fitted with an integral manual release button, allowing the door to be closed without operating the fire alarm.

The Doormouse door holder is surface mounted, and is housed in a white fire resistant ABS casing. Type tested to meet EN1155, knockouts for surface or back cable entry, and a spring loaded pin to give zero residual holding force when de-energised.


The 230Vac unit includes a filter for EMC emissions and is CE marked. Internal diodes dissipate any "back EMF" on switch-off, reducing wear at the control unit.

The Doormouse is ideal for use in any public access areas including hospitals, offices, hotels and nursing homes.



Stephenson Gobin 20 Longfield Road, South Church Enterprise Park, Bishop Auckland, County Durham, UK, DL14 6XB

DOORMOUSE - WALL MOUNTED ELECTROMAGNETIC FIRE DOOR HOLDERS



TECHNICAL INFORMATION				
Supply voltage	24Vdc or 230Vac			
Holding force	200N or 500N			
Power rating	1.15W			
Residual holding force	Zero			
Ambient temperature	0 - 40°C			
Protection	IP 51			
Casing	White fire-res'nt ABS			
Weight	360g / 500g			


Part numbers

200N: 3-87-0370 (24Vdc)

3-87-0371(230Vac) 3-87-0351 (UL - 24V)

3-87-0352 (UL - 230V)

500N: 3-87-0551 (24Vdc)



Item Name	Part number	
Doormouse F.M. bracket	2-34-035G-S001	
Chain keeper	2-31-0308-Z082	

Keeper Plates	Holding Force	Adjustment	Part number
Low profile	200N	15°	2-31-0307-N237
Adjustable	200N	30°	2-31-0310-U005
Adjustable	500N	30°	2-31-0507-U001
Low profile	500N	15°	2-31-0507-Z011

Accessories

Each Doormouse is supplied with an adjustable keeper plate as standard. All other accessories should be sold separately. The Doormouse chain keeper plate can be used where the standard keeper plate will not reach the door holder due to the door being positioned further towards the centre of the wall.