



## GFE-PA-VOX-C

### Conventional PA Speaker Amplifier/ Controller

The GFE-PA-VOX-C is a conventional PA Speaker Amplifier/ Controller which is available in either Red or White housings. The GFE-PA-VOX-C is able to provide a maximum of 24 W of sound output to a single PA Speaker.

The GFE-PA-VOX-C, can broadcast pre-loaded messages. The desired message can be downloaded from our own proprietary recording PC application, via a standard USB interface. This product is controlled by a conventional sounder circuit and externally powered.

TECHNICAL SPECIFICATIONS	
SUPPLY VOLTAGE	Sounder Circuit: 17-30 V DC - External Supply: 20-30 V DC
SOUNDER CIRCUIT - CURRENT	2.0 mA (Sounder Active)
EXTERNAL SUPPLY - CURRENT	5.0 mA (Quiescent) - 1.0 A (Sounder Active)
POWER OUTPUT MAX.	24 Watts rms
MAX. CABLE SIZE	2.5 mm <sup>2</sup>
OPERATING TEMPERATURE	-10°C to 50°C
MAX. HUMIDITY	85% RH Non-Condensing
ENCLOSURE / MATERIAL	White or Red / ABS
PROTECTION CATEGORY	IP44 - Type A - Indoor use
DIMENSIONS	100 (D) x 48 (H) mm
WEIGHT	125 g / 160 g inc. packaging
ORDER CODE	
GFE-PA-VOX-C	CONVENTIONAL PA SPEAKER AMPLIFIER/ CONTROLLER