



GFE-MCPE-C

Conventional Manual Call Point

The GFE-MCPE-C is a Conventional Manual Call Point, designed and manufactured to comply with EN54-11, compatible with all GFE Conventional Control panels. A bi-colour LED flashes Green when the unit is connected to a control panel and is illuminated Red when in Alarm.

The unit is supplied complete with a **hinged flap** which protects the trigger element from accidental activation and reduces malicious activations as **two actions** are required in order to activate the device. This unit can be both surface and flush mounted and it can be easily reset using the supplied key after activation.

TECHNICAL SPECIFICATIONS		
SUPPLY VOLTAGE		20-30 V DC
CURRENT - QUIESCENT		200 uA
CURRENT - DEVICE IN ALARM		50 mA @ 24 V DC - Alarm Resistance 470 Ohms Max.
CABLE SIZE		0.5-2.5 mm ²
COLOUR / CASE MATERIAL		Red / ABS & Clear/ PC - Flame Retardant 94 V0
PROTECTION		IP24D
OPER. TEMPERATURE		-10°C to 55°C
MAX. HUMIDITY		95% RH Non-Condensing
DIMENSIONS		92.6 (W) x 92.6 (H) x 60.1 (D) mm
WEIGHT		152 g
ORDER CODE		
GFE-MCPE-C	1328-CPR-0377	CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-BLUE	1328-CPR-0377	BLUE CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-GREEN	1328-CPR-0377	GREEN CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-YELLOW	1328-CPR-0377	YELLOW CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-WHITE	1328-CPR-0377	WHITE CONVENTIONAL MANUAL CALL POINT