



ORION EX MINI-REP

Orion Mini-Repeater Panel

The ORION EX MINI-REP will provide remote control, system status display and monitoring functions for the ORION EX Extinguishing Panel. All Fire, Fault, Test and Disabled conditions are displayed. User is able to control all functions at access Level's 1 and 2. Compliant with EN54-2. Display and Control Functions are replicated and shown in the same manner as on the ORION EX Fire Detection and Extinguishing Panel. Access to Level 2 is via a four digit code (same code as used on the ORION EX Panel).

It includes as standard an **RS232 interface**. This unit is also compatible with all of GFE's standard data loop interfaces, allowing the ORION MINI-REP panel to be interfaced to an ORION EX Panel using 4 different interfacing technologies:

- ▶ RS232
- ▶ RS485
- ▶ Fibre Optics
- ▶ TCP/IP (specific for ORION EX systems)

A maximum of 4 **ORION EX MINI-REP** panels can be connected to a single ORION EX Panel. When using data loop interfaces, only one repeater panel will offer both control and display of the system. The remainder of the repeater panels will only offer system status display. This unit is available in both white and red colours.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	28 V DC nominal derived from Orion Aux. Supply O/P
SUPPLY CURRENT	40 mA
CONNECTIONS	+Supply, -Supply, TX and RX
REPEATER NETWORK	RS232, RS485, FO or TCP/IP - 1 Display & Control 3 Display Only
HUMIDITY	Max 95% RH Non-Condensing
OPERATING TEMPERATURE	-10°C to 50°C
WEIGHT	1.4 Kg
DIMENSIONS	194 (L) x 256 (W) x 75 (H) mm
COLOUR	White or Red

ORDER CODE

ORION EX MINI-REP	CONVENTIONAL MINI-REPEATER PANEL FOR ORION EX - INCLUDES 1 X RS232 INTERFACE
--------------------------	--