

PM844-A

Power Supply Switch Mode 12VDC-4A higher spec

High efficient switch mode 12 Volt dc Power Supply featuring Mains and Battery Monitoring with two independent volt free fault outputs. Full Rated Current to Load 4 Amp plus 0.5 Amp average for battery charging



Details

- Continuous full rated current to load
- Additional 0.5 A (average) to charge standby battery
- High efficiency electronics for reduced running costs and lower operating temperatures
- Modular construction for ease of maintenance and installation
- Full electronic short circuit and overload protection on load output under mains operation
- Lid opening tamper detection
- Increased room space for additional PCBs or cables
- Deep Discharge Protection
- 2 independent volt free fault outputs
- Reverse battery connection protection
- PSU fault indicator (Red LED)
- Battery Disconnected fault detection

PM844-A

Power Supply Switch Mode 12VDC-4A higher spec

Technical specifications

Electrical

Mains input	100 to 240 VAC
-------------	----------------

Output

Power output voltage	13.8 VDC
Output ripple	150 mV pk-pk max.
Power output current mains	4 A

Battery

Max. Battery capacity	18 Ah 12 V
Battery charge current	0.5 A

General

Fuse(s)	230 VAC input 3.15 A, 12/24 V output 4 A
---------	--

Physical

Colour	White
Form factor	Steel cabinet

Standards & Regulation

Compliance	CE, REACH, RoHS 2, WEEE
------------	-------------------------

Input voltage

100-240 VAC

Frequency

50 - 60 Hz

Output voltage

13.8 VDC nominal

Battery charge current

0.5 A

Load Output

4 A

Output ripple

150 mV pk-pk max

Max. battery size

18 Ah

Fuse 12/24 V output

4 A

Fuse 230 VAC input

3.15 A

Operating temperature

-10 to +40°C at 95% relative humidity noncondensing

Storage temperature

-20 to + 80°C

Weight (excluding battery)

4.30 kg

Dimensions (W x H x D)

355 x 330 x 80 mm

