



EN54-3 Type A  
CERTIFIED  
1328-CPR-0289



## VULCAN 2 C

### Conventional Sounder/ Beacon

The VULCAN 2 C is a low consumption sounder designed to be used as an unobtrusive low profile sounder or as a base sounder to be installed in conjunction with a conventional detector. This leads to reduced installation costs and improves the aesthetics of the fire alarm system.

Four different tones are available and selected by jumpers. The Sound level can be adjusted if required, using the potentiometer.

The complete range is composed of 3 varieties in both base and wall mounted versions: Beacon, Sounder and combined Sounder/ Beacon.

#### TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - QUIESCENT	1.1 mA
ALARM CURRENT - 800 TO 1000 HZ	4 mA sounder only - 5.5 mA inc. Beacon
ALARM CURRENT - 2.0 TO 3.0 KHZ	7 mA sounder only - 8 mA inc. Beacon
ALARM CURRENT BEACON	2.5 mA
SOUNDER OUTPUT - LOW FREQ.	84 dB @ 1 m
SOUNDER OUTPUT - HIGH FREQ.	88 dB @ 1 m
MAX. CABLE SIZE	2.5 mm <sup>2</sup>
OPERATING TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
COLOUR / CASE MATERIAL	White or Red / ABS - Transparent PC
DIMENSIONS	100 (D) x 50 (H) mm
WEIGHT	144 g inc. base
<b>ORDER CODE</b>	
<b>VULCAN 2 CS</b>	VULCAN 2 - CONVENTIONAL BASE SOUNDER
<b>VULCAN 2 CSB</b>	VULCAN 2 - CONVENTIONAL BASE SOUNDER WITH BEACON
<b>VULCAN 2 CB</b>	VULCAN 2 - CONVENTIONAL BEACON
<b>VULCAN 2 L</b>	OPAQUE LID FOR VULCAN 2
<b>VULCAN 2 LT</b>	TRANSPARENT LID VULCAN 2