

## **VULCAN 2 VOX C**

## **Conventional Voice Sounder**

The VULCAN 2 VOX C is a wall mounted Conventional Voice Sounder which is available in either White or Red housings.

The VULCAN 2 VOX C, can broadcast up to 2 differentiated pre-loaded messages: Fire and Alert. The desired messages can be downloaded from our own proprietary recording PC application, via a standard USB interface.

## **Key Features**

- ▶ Multi-Message. Follows Panel's Sounder Programming
- ► Multi-Language
- ▶ 92 dBA maximum output
- ▶ Messages easily programmed via USB interface using dedicated software
- Synchronization for fast activation
- ▶ Compatible with most conventional panels

| TECHNICAL SPECIFICATIONS              |  |
|---------------------------------------|--|
| SUPPLY VOLTAGE                        | 20 V to 30 VDC   |
| SUPPLY CURRENT - SOUNDER ACTIVE       | 28 mA (Average) - 65 mA (Peak) @ 24 VDC                |
| SOUND OUTPUT @ 1 METER                | Tone 88 dBA / Voice message 92 dBA                     |
| TOTAL AUDIO MEMORY SIZE               | 4 minutes (decoded audio) up to 16 min (encoded audio) |
| MAX. CABLE SIZE                       | 2.5 mm <sup>2</sup>                                    |
| OPERATING TEMPERATURE / MAX. HUMIDITY | -10°C to 50 °C / 95% RH Non-Condensing                 |
| COLOUR / CASE MATERIAL                | White or Red / ABS - Transparent PC                    |
| PROTECTION                            | IP21C - Type A - Indoor use                            |
| DIMENSIONS                            | 100 (D) x 29 (H) mm - with Lid 37.5 (H) mm             |
| WEIGHT                                | 127 g - 149 g with Lid                                 |
| ORDER CODE                            |  |
| VULCAN 2 VOX CS                       | VULCAN 2 VOX -CONVENTIONAL VOICE BASE SOUNDER          |
| VULCAN 2 VOX CSB                      | VULCAN 2 VOX -CONVENTIONAL BASE SOUNDER WITH BEACON    |

GFE-05.2015 globalfire.pt