

TS.3204

Contract Closer














See separate brochure for details

Product Overview

Style and performance come together in the TS.3204 Rutland door closer range. Having a power size from EN2,3,4 by position, CE marked, and classified to meet and exceed the European standards make it an ideal door closer for the mid range contracts. These closers are tested to 120 minutes in successful EN 1634 fire tests.

Specification Overview

					
Fire Tested up to 120mins	Max Door Weight 60kg	Opening Angle 180°	Max Door Width 930mm	Adjustable Closing Speed	Rut Lock
					
Universal Application	Power Size EN3	Adjustable Latch Speed	Guarantee 10 YEARS	3204CPR01.07.13	

Technical Information

BS EN 1154 Classification

TS3204 door closers have been independently tested to conform with the EN 1154 performance standard. They are CE marked and classified as follows:

Standard Arm Fig 1.

4	8	3	1	1	3
---	---	---	---	---	---

Parallel Arm Fig 66.

3	8	3	1	1	3
---	---	---	---	---	---

BS EN 1634 Fire Test

TS3204 closers have been tested to EN 1634 for 30, 60 and 120 minute door sets. Test certificates are available on request.

Options

- Hold-Open arm (Not to be used on fire doors)
 - Hollow door fixing pack
 - Drop plate
 - EN 2 & 4 - CE in EN 3 Only
- Options not covered by CE.*

Other Benefits

- Silver and Plated finishes



All dimensions shown are in mm.

