

Brook 2





LED emergency luminaire from Channel Safety Systems



LED Emergency Luminaire

The Brook 2 LED bulkhead can be used either externally or internally owing to its IP65 rating.

Now with increased light output!

Mains LM output320LmEmergency LM output210LmMains Wattage7.3wBatteryNi-cd 3.6v 2000mAhLED20x SMD 5730

Features

- Approximately twice the light output but using 66% less power than a typical 8W fluorescent bulkhead.
- Long life LED technology
- Maintained or non-maintained operation
- Optional self-test operation to BS
 EN 62034
- Polycarbonate construction with clear diffuser
- Hinged gear tray for easy installation
- Cable entry: rear, end & side of fitting
- Self-test option available
- Easy to install
- Low environmental impact
- Low running costs
- Low maintenance
- Meets BS EN 60598-2-22 and other relevant standards




www.channelsafety.co.uk Tel: 0845 884 7000 Email: sales@channelsafety.co.uk

Press once for 5 second monthly test Press twice for 3 hour yearly test LED confirms pass/fail status

Optional Remote Control



Hinged gear tray for easy installation



PHOTOMETRIC SPACING DATA (1 lux)

2.5m 2.6 7.7 8.9 2.9	Mounting height	∄↔]		$\stackrel{\square}{\longleftrightarrow}$	
	2.5m	2.6	7.7	8.9	2.9
4m 2.6 7.9 8.9 2.7	4m	2.6	7.9	8.9	2.7

SPECIFICATIONS			
Light Source	20x LED SMD 5730		
IP Rating		IP65	
Emergency Duration		3 hours (minimum)	
Mains Voltage		230V 50Hz ± 10%	
Mains Current (max)		75mA (max) 40mA quiescent (18W)	
Recharge Period		Less than 24 hours	
Charge Indicator		Integral green LED	
Changeover Voltage		As per the requirements of BS EN 60598-2-22	
Temperature Range		0°C to 40°C	
Weight		950g	
Battery		3.6V 1.5Ah Nickel Cadmium	
	DECOND	7.01	
PRODUCT CODE	DESCRIPTION		
E/BK/M3/LED/2	Brook self contained 3 hour maintained emergency LED light		

E/BK/M3/LED/2	Brook self contained 3 hour maintained emergency LED light
E/BK/M3/LED/2/ST	Brook self contained, self-test 3 hour maintained emergency LED light
E/BZ/KIT/BROOK/WH	Brook semi-recessing bezel
E/PIC/ME/LED/PACK	Brook Pictogram Pack AD/AL/AR/AU
B/BATT/BROOK/2	Brook Battery- 3 cell NiCd
E/EM/RC	Optional Remote Control

Errors & ommissions excluded. Specification is subject to change without notice. revision 013-1