

HORIZON LED EMERGENCY BULKHEAD



This LED Surface Mounted Emergency Bulkhead offers a modern and contemporary design and is manufactured in Europe. An optional recessing kit and drop legend are available making this a versatile fitting.

awex
EMERGENCY LIGHTING

DATA SHEET



230V

LED

IP65


3 YEAR
GUARANTEE

Modern and contemporary design

Clear plexiglass diffuser for improved light output


European manufacture

Dimensions (mm)



RECESSING CUT (mm):

- wall
- ceiling



125 x 260

Specification

Input Voltage:	220-240V AC, 50-60Hz
Wattage:	1W / 2W
Emergency Duration:	3 hours
Mode of Operation:	Maintained / Non-maintained
Working Temperature:	0°C - 40°C
Tested To:	BS EN 60598-2-22 BS EN 60598-1
Material:	Polycarbonate body
Emergency Lumen Output:	1W - 130lm 2W - 250lm

*Guarantee excludes all batteries which have a 12 month guarantee

Version 2.09/2021



BLE LIGHTING AND POWER LTD
Unit 3, Drake Business Park
Drake House Crescent, Sheffield, S20 7HT

T: 01246 432325 F: 01246 432324
E: sales@blelighting.co.uk
www.blelighting.co.uk

Additional Information

- 3.6V NiCD Battery
- 24 hour recharge time
- Deep discharge protection
- Surface mounted
- Plexi glass and white polycarbonate body
- LED indicator
- Supplied with ISO Universal Exit Legend Sticker
- Recessing kit available
- Drop legend available
- European Manufacture
- Suitable for internal and external use
- Class II

Code	Description	Dimensions (L x W x D mm)
HORIZON 1W LED M	HORIZON 1W LED Surface Mounted Emergency Bulkhead	276 x 143 x 44
HORIZON 2W LED M	HORIZON 2W LED Surface Mounted Emergency Bulkhead	276 x 143 x 44
HORIZON LGD	Drop Legend with ISO Universal Sticker	
HORIZON R/KIT	Recessing Kit	

PRODUCT REFERENCE	MOUNTING HEIGHT (M)	TRANSVERSE TO WALL (M) 	TRANSVERSE SPACING (M) 	AXIAL TO WALL (M) 
1W	2.50	3.50	8.00	3.50
	3.00	3.00	8.50	3.00
	3.50	3.00	9.00	3.00
	4.00	3.00	9.00	3.00

PRODUCT REFERENCE	MOUNTING HEIGHT (M)	TRANSVERSE TO WALL (M) 	TRANSVERSE SPACING (M) 	AXIAL TO WALL (M) 
2W	2.50	4.50	10.50	4.50
	3.00	4.00	11.50	4.00
	3.50	4.00	12.00	4.00
	4.00	4.50	12.50	4.00